

TERMINAL PRENSADO FLANGE 45°



Terminal sem solda

CODIGO M2A407


M - Macoflan

2 - Trama 2 Tramas --- 4 Tramas ---- 6 Interlock

A - Aço Carbono ---- I Aço Inox

4- curva 45 graus

07 - Código 61---- 3000psi



3000 psi (cód. 61)

Ø		Ø nommal flange	medidas					
pol	traço		H	L	K	A	D	
1/2"	-8	-8	62	95	22	30,2	7	M2A407-08-08
5/8"	-10	-8	70	102,5	23	30,2	7	M2A407-08-10
5/8"	-10	-12	79,5	115,5	25	38,0	7	M2A407-12-10
3/4"	-12	-12	86,5	127,5	27	38,0	7	M2A407-12-12
3/4"	-12	-16	90	132	27	44,5	8,2	M2A407-16-12
1"	-16	-16	107,5	162,5	33	44,5	8,2	M2A407-16-16
1"	-16	-20	108,5	163,5	40,5	50,8	8,2	M2A407-20-16
1.1/4"	-20	-20	136,5	197,5	47	50,8	8,2	M2A407-20-20
1.1/4"	-20	-24	136,5	197,5	47	60,4	8,2	M2A407-24-20
1.1/2"	-24	-24	162	232,5	50	60,4	8,2	M2A407-24-24
2"	-32	-32	210,5	286,5	56	71,4	9,7	M2A407-32-32

CODIGO M2A417


M - Macoflan

2 - Trama --- 2 Tramas --- 4 Tramas ---- 6 Interlock

A - Aço Carbono ---- I Aço Inox

4 - curva 45 graus

17 - Código 62 ----6000 psi



6000 psi (cód. 62)

Ø		Ø nommal flange	medidas					
pol	traço		H	L	K	A	D	
1/2"	-8	-8	63	96	22	31,8	8	M2A417-08-08
5/8"	-10	-8	76	112	23,5	31,8	8	M2A417-08-10
5/8"	-10	-12	81,5	117,5	24	41,2	9	M2A417-12-10
3/4"	-12	-12	89,5	130,5	28	41,2	9	M2A417-12-12
3/4"	-12	-16	95,5	136,5	28	47,8	9,6	M2A417-16-12
1"	-16	-16	112	167	37	47,8	9,6	M2A417-16-16
1"	-16	-20	116,5	171,5	37	53,9	10,4	M2A417-20-16
1.1/4"	-20	-20	138,5	200	52	53,9	10,4	M2A417-20-20
1.1/4"	-20	-24	143	203,5	52	63,5	12,7	M2A417-24-20
1.1/2"	-24	-24	162,5	233	58	63,5	12,7	M2A417-24-24
2"	-32	-32	212,5	289	65	79,4	12,7	M2A417-32-32